

AXLES

Customer Name											
Beam Only					Axle Beam Round Diameter:						
					2K = 1-3/4"		3.5K = 2-3/8"				
					3.5K=3" Special Order						
					5.2 - 7K = 3"		8K = 3"				
					10K = 4"		12K/16K = 5"				
Spring Axle											
Customer Part Number											
Model #	2K	3.5K	4.4K	5.2K	6K	7K	8K	10K	12K	16K	
Axle Capacity											
Spindle Style											
			Straight		4" Drop			4" Drop up to 8K			
Lubrication Type (if grs)											
			Standard			Super Lube/Zerk					
Fluid Type											
			Oil			Grease					
Axle Type											
			Brake			Idler					
Brake Type											
		Electric	Disc	Hydraulic	Electric, Self Adjust			Air (12-16K)			
Brake Flange, Opt on 2K & 3.5K											
			Yes			No					
Tube Type											
			Standard			Heavy Wall					
Camber											
			Yes			No					
Bolt Pattern											
		Brake		475	545	550	555	655	865	8/275mm	
		Idler	440	475	545	550	555	655	865		
Stud Size											
		1/2"	5/8"	9/16"	M22						
Hub Face Dimension											
See Below											
Spring Center Dimension											
See Below											
Spring Orientation											
			Overslung			Underslung					
Spring Type											
			Double Eye			Slipper			No Springs		
Spring Length, Eye to Eye No Load											
		20"	23"	25"							

