

## AXLES

Customer Name																	
Beam Only				<b>Axle Beam Round Diameter:</b>													
				2K = 1-3/4"		3.5K = 2-3/8"											
				3.5K=3" Special Order													
				5.2 - 7K = 3"		8K = 3"											
				10K = 4"		12K/16K = 5"											
<b>Spring Axle</b>																	
Customer Part Number																	
Model #	2K	3.5K	4.4K	5.2K	6K	7K	8K	8K HYB	10K	12K	16K						
Axle Capacity																	
Spindle Style																	
				Straight		4" Drop		4" Drop up to 8K									
Lubrication Type (if grs)																	
				Standard		Super Lube/Zerk											
Fluid Type																	
				Oil		Grease											
Axle Type																	
				Brake		Idler											
Brake Type																	
		Electric		Disc		Hydraulic		Electric, Self Adjust		Air (12-16K)							
Brake Flange, Opt on 2K & 3.5K																	
				Yes		No											
Tube Type																	
				Standard		Heavy Wall											
Camber																	
				Yes		No											
Bolt Pattern																	
		Brake		475		545		550		555		655		865		8/275mm	
		Idler		440		475		545		550		555		655		865	
Stud Size																	
		1/2"		5/8"		9/16"		M22									
Hub Face Dimension																	
See Below																	
Spring Center Dimension																	
See Below																	
Spring Orientation																	
				Overslung		Underslung											
Spring Type																	
				Double Eye		Slipper		No Springs									
Spring Length, Eye to Eye No Load																	
		20"		23"		25"											

