

AXLES

Customer Name											
Beam Only (With Springs)			Beam Only (No Springs)			Axle Beam Round Diameter: 2K = 1-3/4" 3.5K = 2-3/8" 3.5K=3" (Special Order) 5.2 - 7K = 3" 8K = 3" 10K = 4" or 5" 12K/16K = 5"					
Customer Part Number											
Model #	2K	3.5K	4.4K	5.2K	6K	7K	8K	8K HYB	10K	12K	16K
Axle Capacity											
Spindle Style			Straight			4" Drop (Up to 8K)					
Lubrication Type (if grs)			Solid Cup Standard			Super Lube/Zerk					
Fluid Type			Oil			Grease					
Axle Type			Brake			Idler					
Brake Type			Disc Hydraulic Electric Electric, Self Adjust Electric, Self Adjust ABS								
Brake Flange, Opt on 2K & 3.5K			Yes			No					
Tube Type			Standard			Heavy Wall					
Camber			Yes			No (Not Recommended)					
Bolt Pattern			Brake	475	545	550	555	655	865	8/275mm	
			Idler	440	475	545 (2K - 5.5")		545 (2K/4.4K - 6.5")		550	555
Stud Size			1/2"			5/8"	9/16"	M22			
Hub Face Dimension					Spring Center Dimension					See Below	
Spring Orientation			Overslung			Underslung					
Spring Seat 10K-16K			Fixed			Adjustable			Hutch Style		
Spring Type			Double Eye			Slipper	HDSS DBL Slipper			No Springs	
Spring Length, Eye to Eye No Load			20"	23"	25"		Other (Specify)				
Tube Coating			Powder Coat Black			Raw					

